



**EQOSHADE<sup>®</sup>**

**EXTERIOR ROLLER SCREENS**



- EQOSHADE® provides quality eco-protection solutions that **reduce energy consumption**, allowing for a more **comfortable** life style.

- **Reducing the need** for air-conditioning and heating, controlling the movement of heat and sunlight in a building through keeping the heat in during winter and out during the summer.

- Introducing the the Ego Screen, trust EQOSHADE® to find the perfect shade for windows, decks, balconies, terraces, and even gardens in a size, shape, color and **convenience** you will love.

For other products and services, please visit:  
[www.eqoshade.com](http://www.eqoshade.com)

## CONTENT

---

**Where to install  
eco-protection?** **03**

---

**EQOSHADE®  
Screens** **04**

**EQO Screen** **05**  
Screen with cable guide

---

### Options

**Fabric** **06**

**Technical Details** **07**

**Tenara Thread** **08**

**Motor** **09**

---


**References** **10**



**Protect what  
you value.**

[info@eqoshade.com](mailto:info@eqoshade.com)

# WHERE TO INSTALL EXTERIOR ROLLER SCREENS?




# EQO SCREEN

This eco-protection system is ideal for both interior and exterior use and ensures effective light control while **protecting privacy**.

In addition to their highly decorative aspect, this screen offers other benefits such as providing **energy savings** by reducing interior temperatures, protecting property and people from ultra-violet rays, and creating a more comfortable environment.

<b>Roller</b>	Ø78 mm anodized aluminium T6 roller tube / 2.3 mm thick
<b>Front bar</b>	Ø40 mm stainless-steel 304 front bar / 1.2 mm thick
<b>Stainless steel wire</b>	Ø5 mm stainless-steel 316 6mm
<b>Fabric</b>	Suntex® 95 with GORE® Tenara® sewing
<b>Mounting</b>	Ceiling, wall
<b>Operation</b>	Manual (hand crank), motorized, automated
<b>Frame Warranty</b>	3 years
<b>Fabric Warranty</b>	10 years
<b>Maximum Size(Manual)</b>	Width: 4M X Height: 4M
<b>Maximum Size(Powered)</b>	Width: 3M X Height: 6M (Less height allows for wider screens)





# FABRIC OPTIONS

## Fabric options for **EQOSHADE®** SCREEN RANGE

**Content:** Vinyl coated polyester

**Width:** 126" (3200mm)


**Weight:** Approx. 15.4oz. per square yard

**Openness factor:** Approx. 5%


### Features

- Infused with Microban® antimicrobial technology that continuously inhibits that growth of stain-causing bacteria, mold and mildew.
- Durable, dimensionally stable, lead-free and printable
- Approved by the Melanoma International Foundation for its effectiveness in preventing sun damage on skin and eyes.
- Flame retardant (NFPA 101)
- Easy to clean
- 10 year limited warranty


Phifer  
**SunTex® 95**




SUNTEX® 95 WHITE




SUNTEX® 95 WHITE GREY




SUNTEX® 95 ALPACA



SUNTEX® 95 MOCHA




SUNTEX® 95 DARK BRONZE



SUNTEX® 95 BLACK

# TECHNICAL DETAILS

PHOTO	PART NO.	PART NAME
	1	NYLON JACKET
	2	STAINLESS STEEL WALL BRACKET
	3	FRONT BAR END CAP
	4	SWAGE FORK
	5	MINI PIPE TURNBUCKLE JAW SWAGE 5MM
	6	GEAR BOX
	7	70MM SQUARE END PLUG
	8	70MM ROUND END PLUG
	9	78MM ANODIZED ALUMINUM ROLLER TUBE
	10	STAINLESS-STEEL 5MM CABLE
	11	STAINLESS STEEL FRONT BAR
	12	HAND CRANK
	13	FLOOR/WALL MOUNT



# TENARA THREAD

## Unaffected by Sunlight

- Maintains strength after regular exposure to UV
- UV resistance is built-in, NOT a coating or additive

## Weather-Proof


- Flexible and strong in extreme hot and cold
- Does not absorb water
- Resists acid rain, salt water, pollution, snow and freezing

## Easy to Clean

- Unaffected by acids, alkaline solutions, bleach and cleaning chemicals
- Does not stain

## Colors Will Not Fade

- GORE® TENARA® Sewing Thread is pigmented-not dyed
- GORE® TENARA® Sewing Thread is extremely color-fast\*\*







# POWERED OPTIONS

SERIES	ERESFN1060-50-BI
Length without bracket	840
Motor diameter	45mm
Input voltage	230 V / 50Hz
Power	205 W
Rated torque	50 Nm
Maximum load	113 kg
Rated RPM	12 rpm
Current consumption	0.89 A
Power on duration	4 min
Number of wires	3
Protection type, VDE 700	IP44
Cable length	2.0 m
For shaft diameter	60mm octagonal shaft
Application	Awnings, rescue windows and escape doors
Features	<p>Simple electronic limit position adjustment via emitter</p> <p>Permanent preservation of the limits in case of power failure</p> <p>Manual override function</p> <p>Built-in receiver, radio code BI</p> <p>Easy control via our emitters with radio code BI</p> <p>Voice control via Google Home, Alexa, Bixbi and Siri (heicko smart stick or smart box required)</p> <p>5-year limited warranty</p>
Crank (manual use)	



## Features


- Simple position limit adjusted through emitter
- Permanent preservation of the set limits in case of power failure
- Manual override function
- Built-in receiver, radio code BI
- Voice control via Google Home, Alexa, Bixbi and Siri (Heicko smart stick or smart box required)



# REFERENCES



Mercure Hotel, Bangkok



Sofitel Sukhumvit, Bangkok

-Baan Amphur - Pattaya

-Club House - Hong Kong

-The Spa - Koh Samui

-Mercure Hotel - Bangkok

-Meridien Survanabhumi - Bangkok

-Sofitel Sukhumvit - Bangkok

-Bearing - Bangkok

-The Peninsula - Bangkok



Private Residence, Bangkok



Baan Amphur, Pattaya



The Spa, Koh Samui



Peninsula, Bangkok

EQOSHADE®

[www.eqoshade.com](http://www.eqoshade.com)

